

Spray Lacquer



Dy-Mark's **Spray Lacquer** is a lightfast and durable paint designed for colour coding and for use with stencils. **Spray Lacquer** is suitable for use on metal and timber, with the colour range matched to Australian steel industry standards.

DIRECTIONS FOR USE

Preparation

Shake can for at least 20 seconds after the mixing ball begins to rattle.

Application

Hold can upright or in the inverted position and spray with the nozzle 15 – 20cm from the surface. For best results, spray the surface using a side-to-side motion.

TECHNICAL DATA

Size:	350g Aerosol
Finish:	Matt
Colour:	17 Standard Colours; 6 Fluoro Colours
Consistency:	Liquid
Coverage:	Approximately 2 sqm per can (depending on surface)
Suitable Surfaces:	All surfaces
Drying Time:	10 minutes at 25°C
Ideal Application Temperature:	Between 5°C and 40°C

STORAGE

Store below 50°C. Do not store in direct sunlight or in vehicles under hot conditions. Protect aerosol cans against physical damage.

DISPOSAL

Aerosol should be completely emptied prior to disposal. Contents of can are under pressure. Do not puncture or incinerate even when empty. When empty, dispose of this container through an approved recycling scheme or seek advice from your local council regarding accepted disposal methods.

SAFETY INFORMATION

HIGHLY FLAMMABLE

Keep away from flame, heat and sources of ignition. Do not smoke and ensure adequate ventilation during use. Can be harmful by inhalation, in contact with skin and if swallowed. Intentional misuse by deliberately inhaling contents can be harmful or fatal. Please note that the slip resistance and performance of this product depends on many factors outside the control of Dy-Mark; including surface preparation, correct application and environmental conditions. Dy-Mark recommends a risk assessment prior to use to determine if the product is suitable to the:

- Slip resistance required
- Surface type
- Volume of traffic
- Potential exposure to any surface contaminants e.g. water, solvents or chemicals

For more information regarding the product's slip resistance, please contact the Dy-Mark Sales and Customer Support Centre on 1300 396 275.

FIRST AID

KEEP OUT OF REACH OF CHILDREN

If swallowed: Do not induce vomiting.

Eye contact: In case of contact with eyes, rinse immediately with plenty of water. Seek medical advice from your doctor or Poisons Information Centre (**Australia: 13 11 26; New Zealand: 0800 764 766**).

Note: the information provided within this Technical Data Sheet is intended as a guide only. The performance of this product will depend on many factors outside the control of Dy-Mark; including surface type and environmental conditions. Refer to Material Safety Data Sheet for more information.