



Industrial  
Packaging



## Strapping

# P.E.T. (Polyester) Strapping

### Features and Benefits

- Ideally suited for rigid loads that require strapping tension throughout handling, shipping and storage
- Easy to handle with no sharp edges and does not whiplash when removed
- Reduces machine downtime due to less frequent core changes
- Does not rust therefore does not stain or mark goods' surfaces
- P.E.T. strap can be tensioned up to 50% more than polypropylene strap of equivalent size
- Performs well under 'shock' loading and takes 2.5 times the energy to break as steel



P.E.T. (Polyester) Strapping	Ref. Code
● P.E.T (Polyester) Strapping 12x2400 0.5mm Embossed	35260112
● P.E.T (Polyester) Strapping 16x1170 0.9mm Embossed	35260116
● P.E.T (Polyester) Strapping 19x800 1.0mm Embossed	35260119
● P.E.T (Polyester) Strapping 16x1050 0.9mm Smooth	35260216
● P.E.T (Polyester) Strapping 19x880 0.9mm Smooth	35260219

### P.E.T. (Polyester) Strapping Specifications

Product Code	Description	Size	Breaking Load	Gauge
35260112	P.E.T (Polyester) Strapping - Embossed	12mm x 2400m	260kg	0.5mm
35260116	P.E.T (Polyester) Strapping - Embossed	16mm x 1170m	518kg	0.9mm
35260119	P.E.T (Polyester) Strapping - Embossed	19mm x 800m	715kg	1.0mm
35260216	P.E.T (Polyester) Strapping - Smooth	16mm x 1050m	598kg	0.9mm
35260219	P.E.T (Polyester) Strapping - Smooth	19mm x 880m	718kg	0.9mm

### NATIONAL SALES & ENQUIRIES

Ph: 1300 396 275 • Fax: 1300 360 440 • E-mail: [sales@dymark.com.au](mailto:sales@dymark.com.au) • Web: [www.dymark.com.au](http://www.dymark.com.au)

