



# TREADRITE™



## Slip Resistant Coating

350g | Qty 12 | 1L, 4L & 10L | Qty 1

### Features & Benefits

- Ideal for interior and exterior untreated timber, concrete, primed metal and brick & clay pavers
- Creates durable slip resistant surfaces
- Resists cracking, peeling and exposure to petrol, oil and mild chemicals
- Easy to apply with uniform coverage
- Industrial applications include stairs, entrances and exit ways
- TreadRite™ (350g) has been tested for compliance with AS 4586:2013, Slip resistance of new pedestrian surface materials (classification P4). **Not suitable for use on ramps.**
- TreadRite™ (1L, 4L and 10L) have been tested for compliance with AS 4586:2013, Slip resistance of new pedestrian surface materials (classification P5). **Suitable for use on ramps.**



#### Suitable Surfaces

Untreated timber, concrete, primed metal and brick & clay pavers



#### Coverage Aerosol Spray

Approximately 1.3–1.7sqm per aerosol can (depending on surfaces)

#### Brush On

Safety Yellow – approx. 3–6sqm  
Clear & Black – approx. 5–10sqm



#### Drying Time Aerosol Spray

Touch Dry 1–2 hours (25°C).  
Recoat after 2 hours.  
Walk on 24–48 hours.

#### Brush On

Touch dry 6–8 hours (25°C).  
Recoat 24–36 hours (depending on film thickness).  
Walk on in 24–48 hours.



#### Ideal Application Temperature

Between 10°C and 40°C

#### TreadRite™ (Inverted Use)

Clear	350g	12	23063500
Black	350g	12	23063501
Yellow	350g	12	23063505
White	350g	12	23063511



Inverted Spray

#### TreadRite™ (Brush On)

Clear	1L	1	23060100
Black	1L	1	23060101
Yellow	1L	1	23060105
White	1L	1	23060111
Clear	4L	1	23060400
Black	4L	1	23060401
Yellow	4L	1	23060405
White	4L	1	23060411
Clear	10L	1	23061000
Black	10L	1	23061001
Yellow	10L	1	23061005
White	10L	1	23061011

WATCH THE VIDEO ON 

