

# TECHNICAL DATA SHEET

Dy-Mark (Aust) Pty Ltd

PO Box 1556 Toowong 4066

Phone: 1300 396 275 Fax: 1300 360 440

[www.dymark.com.au](http://www.dymark.com.au)



## Dy-Mark® SPRAY & MARK®



**Dy-Mark® Spray & Mark®** is a premium marking out paint designed for a range of applications including construction, landscaping, civil works and surveying.

**Spray & Mark®** is suitable for use with the **Long Arm Handle** and **2-Wheel Spot Marking Handle**, also available from Dy-Mark®.

### DIRECTIONS FOR USE

#### Suitable Surfaces:

Concrete, bitumen, steel and timber.

#### Ideal Application Temperature:

Between 5°C and 40°C. Avoid use in windy conditions.

#### Before Spraying:

**Shake can** for at least 45 seconds **AFTER** the mixing ball begins to rattle. Shake can occasionally during use.

#### Application:

Hold can in the **INVERTED** position (upside down), approximately 10-15cm from the surface. Spray width can be adjusted by moving closer or further from the surface to be sprayed.

#### Coverage:

Will produce 200+ 'X' marks, up to 120 linear metres (depending on surface and colour used).

#### Drying Time:

Touch dry in 5 minutes (25°C).

Drying will be slower in cold and humid conditions, in the absence of ventilation or where heavy film build is applied.

#### After Spraying:

**Prevent blocking** by holding the can **UPRIGHT** and spraying until only clear gas escapes. Also **wipe spray tip** of nozzle clean. **Clean up** wet paint with Acetone or General Purpose Thinner.

#### Caution:

Painted surfaces may become slippery when wet. Refer to disclaimer on page 3.

# TECHNICAL DATA SHEET

Dy-Mark (Aust) Pty Ltd

PO Box 1556 Toowong 4066

Phone: 1300 396 275 Fax: 1300 360 440

[www.dymark.com.au](http://www.dymark.com.au)



## TECHNICAL DATA

<b>Size:</b>	350g Aerosol
<b>Colour:</b>	8 Standard and 8 Fluoro colours
<b>Finish:</b>	Matt
<b>Consistency:</b>	Liquid
<b>VOC:</b>	1. Hydrocarbon / Dimethyl ether formula: VOC <620g/L  2. Hydrocarbon formula: VOC <495g/L
<b>Propellant:</b>	1. Hydrocarbon / Dimethyl Ether: SDS no: 18-3984 (Standard colours) SDS no: 18-3983 (Fluoro colours)  2. Hydrocarbon: SDS no: 5495-51 (All colours)

## STORAGE

**Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C. Store in a well-ventilated place.**

**Extremely flammable aerosol. May burst if heated. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.**

**Never leave aerosols inside a car, ie on dashboards and in boots or in any other enclosed vehicle. The internal temperature of the vehicle can be up to 30°C hotter than the outside temperature.**

**If an aerosol is kept near a heat source, the pressure in the can increases rapidly to levels that exceed the can design limits and may cause the can to burst.**

## DISPOSAL

Dispose of contents/empty aerosol container according to regional regulations. Spray unwanted paint onto a newspaper, allow to dry and dispose of via domestic waste collection. Empty aerosol cans are recyclable via steel can recycling programs.

# TECHNICAL DATA SHEET

**Dy-Mark (Aust) Pty Ltd**

PO Box 1556 Toowong 4066

Phone: 1300 396 275 Fax: 1300 360 440

[www.dymark.com.au](http://www.dymark.com.au)



## FIRST AID/SAFETY INFORMATION

**Please refer to Safety Data Sheet before use.** To view the correct SDS please refer to the back of the can under the section "CONTAINS:" to confirm which formulation is used and match up the details with Section 3 of the SDS which contains the formulation.

Safety data sheets are available for download from our website [www.dymark.com.au](http://www.dymark.com.au) or from following QR code:



**Call a POISON CENTRE: Australia 13 11 26, New Zealand 0800 764 766** or doctor/physician if you feel unwell.

Intentional misuse by deliberately inhaling contents can be harmful or fatal.

**KEEP OUT OF REACH OF CHILDREN.**

## DISCLAIMER

The information provided within this Technical Data Sheet is intended as a guide only. The slip resistance and performance of this product depends on many factors outside the control of Dy-Mark®; including surface preparation, surface-specific conditions, surface types, correct application and environmental conditions.

Dy-Mark® recommends customers undertake their own risk assessment prior to use to determine the suitability of the product for the particular use intended. Some factors to consider:

- Slip resistance required
- Surface type
- Volume of traffic
- Potential exposure to any surface contaminants eg. Water, solvents or chemicals

It is essential that a sample of the product be applied to the intended area of use to ensure it is acceptable in appearance and finish and that it performs on the specific surface.

For further information please contact the Dy-Mark® Sales and Customer Support Centre on 1300 396 275.