

# TECHNICAL DATA SHEET

Manufactured in Australia for  
Dy-Mark (Aust) Pty Ltd

www.paintworx.net.au

# paintworx®



## PAINTWORX® WATER-BASED

**Paintworx® Water-Based** is a high quality, quick drying acrylic based paint. It is suitable for DIY interior and exterior decorative projects around the home. Its specially developed water based formula has a low VOC content, low odour and lower toxicity. It has a high gloss finish, excellent adhesion and high durability. Ideal for painting furniture, household accessories, arts & crafts.

### DIRECTIONS FOR USE

#### SUITABLE SURFACES

Metal, wood and plastics when used with appropriate primer. Even suitable for use on polystyrene.

#### IDEAL APPLICATION TEMPERATURE

Between 10°C and 30°C. Avoid use in windy conditions.

#### PREPARATION

Surface should be clean, dry and free from contaminants such as rust, oil, grease, dirt and salt. Thoroughly sand new metal and lightly sand previously painted surfaces to ensure maximum adhesion. For superior protection and adhesion on timber and bare ferrous metals such as steel and iron use appropriate primer. For non-ferrous metals such as aluminium, copper, brass and stainless steel use Etch Primer. For plastics use a Plastic Primer. Note: Adhesion to some plastics like Polyethylene may be difficult. Test the plastic projects on an inconspicuous area first.

#### APPLICATION

Before spraying, cover surrounding areas to protect from overspray. **Shake can** for at least 45 seconds **AFTER** the mixing ball begins to rattle. Shake can occasionally during use. Hold can upright approximately 20-25cm from the surface. Spray with a smooth sweeping motion. To prevent paint from sagging, apply several light mist coats rather than one heavy coat.

Adjust nozzle to achieve desired spray pattern. Use horizontal setting to spray up and down and the vertical setting to spray left to right. (refer to diagram below).



#### COVERAGE

Approximately 1.7m<sup>2</sup> per can (depending on the surface, colour used and amount of overspray).

#### DRYING TIME

Touch dry in 30 minutes (25°C). Recoat within 1 hour or after 24 hours. Drying will be slower in cold and humid conditions, in the absence of ventilation or where heavy film build is applied.

# TECHNICAL DATA SHEET

Manufactured in Australia for  
Dy-Mark (Aust) Pty Ltd

[www.paintworx.net.au](http://www.paintworx.net.au)

# paintworx®

## AFTER SPRAYING

**Prevent blocking** by holding the can upside down and spraying until only clear gas escapes. Also **wipe spray tip** of nozzle clean.

\* **Clean up wet** paint with **water** during the first minutes of drying. Clean up dry paint with General Purpose Thinner.

## TECHNICAL DATA

**Size:** 300g Aerosol

**Finish:** Flat & Gloss

**Colour:** Colour range

**Consistency:** Liquid

**VOC Level:** <470 g/L

**Clean Up:** \* **Clean up wet** paint with **water** during the first minutes of drying. Clean up dry paint with General Purpose Thinner

## STORAGE


Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

## DISPOSAL

Dispose of contents/empty aerosol container according to regional regulations. Spray unwanted paint onto newspaper, allow to dry and dispose of via domestic waste collection. Empty aerosol cans are recyclable via steel can recycling programs.

## FIRST AID / SAFETY INFORMATION

Please refer to Safety Data Sheet before use. Safety data sheets are available from our website [www.dymark.com.au](http://www.dymark.com.au) or from the following QR code:



**Call a POISON CENTRE: Australia 13 11 26, New Zealand 0800 764 766** or doctor/physician if you feel unwell.

Intentional misuse by deliberately inhaling contents can be harmful or fatal.

**KEEP OUT OF REACH OF CHILDREN**

# TECHNICAL DATA SHEET

Manufactured in Australia for  
Dy-Mark (Aust) Pty Ltd

[www.paintworx.net.au](http://www.paintworx.net.au)

**paintworx**<sup>®</sup>

## DISCLAIMER

The information provided within this Technical Data Sheet is intended as a guide only. The performance of this product will depend on many factors outside the control of Dy-Mark<sup>®</sup>; including surface preparation, surface-specific conditions, surface types, correct application and environmental conditions.

Dy-Mark<sup>®</sup> recommends customers undertake their own risk assessment prior to use, to determine the suitability of the product for the particular use intended.

It is essential that a sample of the product be applied to the intended area of use to ensure it is acceptable in appearance and finish and that it performs on the specific surface.

For further information please contact the Dy-Mark<sup>®</sup> Sales and Customer Support Centre on 1300 396 275.