

TECHNICAL DATA SHEET

Dy-Mark (Aust) Pty Ltd

PO Box 1556 Toowong 4066

Phone: 1300 396 275 Fax: 1300 360 440

www.dymark.com.au



Dy-Mark PROTECH® DRY PTFE LUBRICANT



Dy-Mark PROTECH® Dry PTFE Lubricant is a multi-purpose dry film lubricant. It will penetrate and bond to metal, wood, rubber and most surfaces and will form a non-staining micro thin film that prevents sticking, reducing friction and wear. It will seal out moisture, inhibit corrosion and resists oil, dust and dirt build up. Will not melt, freeze or wash off.

DIRECTIONS FOR USE

Recommended Uses:

Hinges, chains, window tracks, locks, conveyers, cutting blades, saw blades, sliding drawers, sliding doors, and other uses.

Application:

Shake can for at least 45 seconds **AFTER** the mixing ball begins to rattle. Shake can occasionally during use. Clean and dry surface area thoroughly. Spray can in **UPRIGHT** position only. Spray light even film directly onto surfaces.

Leave film to dry minimum 10-15 minutes. Full cure in 24 hours. Repeat application when needed for long term dry film lubrication and protection, allowing it to dry between applications.

TECHNICAL DATA

Size:	150g Aerosol
Colour:	Clear
Consistency:	Dry Film
Propellant:	DME

STORAGE

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

DISPOSAL

Dispose of contents/container according to regional regulations.

TECHNICAL DATA SHEET

Dy-Mark (Aust) Pty Ltd

PO Box 1556 Toowong 4066


Phone: 1300 396 275 Fax: 1300 360 440

www.dymark.com.au



FIRST AID / SAFETY INFORMATION

Please refer to Safety Data Sheet before use. Safety data sheets are available from our website www.dymark.com.au or from the following QR code:



Call a POISON CENTRE: Australia 13 11 26, New Zealand 0800 764 766 or doctor/physician if you feel unwell.

Intentional misuse by deliberately inhaling contents can be harmful or fatal.

KEEP OUT OF REACH OF CHILDREN.

DISCLAIMER

The information provided within this Technical Data Sheet is intended as a guide only. The performance of this product will depend on many factors outside the control of Dy-Mark; including surface preparation, surface-specific conditions, surface types, correct application and environmental conditions.

Dy-Mark recommends customers undertake their own risk assessment prior to use, to determine the suitability of the product for the particular use intended.

It is essential that a sample of the product be applied to the intended area of use to ensure it is acceptable in appearance and finish and that it performs on the specific surface.

For further information please contact the Dy-Mark Sales and Customer Support Centre on 1300 396 275.