

TECHNICAL DATA SHEET



Dy-Mark (Aust) Pty Ltd

PO Box 1556 Toowong 4066

Phone: 1300 396 275 Fax: 1300 360 440

www.dymark.com.au

Dy-Mark GRAFFITI REMOVER



Dy-Mark Graffiti Remover features a citrus based formulation that has been specifically designed to remove graffiti without causing damage to the original surface. This product will remove most aerosol paints and inks and is also effective in the removal of adhesive and chewing gum.

DIRECTIONS FOR USE

Suitable Surfaces:

Porous (cement, bricks, stone), Non-porous (metals, glass, reflective signs, glazed ceramic tiles).

Application:

Painted Surfaces: Test a small area to determine the ease / difficulty of removal. Spray directly onto graffiti, allowing approximately 30 seconds for remover to attack the surface. Wipe off with a clean rag, ensuring the soiled rag does not come back into contact with the surface. A damp soapy rag will assist with removal. Sensitive areas should be treated immediately with a soft cloth, working on small sections at a time.

Porous Surfaces: Remove graffiti as per painted surfaces; however use of a pressure washer, steel wool or a stiff bristle brush may be required.

TECHNICAL DATA

Size: 400ml Spray

Consistency: Liquid

STORAGE

Store in well-ventilated place. Keep cool. Store locked up. Keep container tightly closed.

DISPOSAL

Dispose of contents/container according to regional regulations.

TECHNICAL DATA SHEET

Dy-Mark (Aust) Pty Ltd

PO Box 1556 Toowong 4066


Phone: 1300 396 275 Fax: 1300 360 440

www.dymark.com.au



FIRST AID / SAFETY INFORMATION

Please refer to Safety Data Sheet before use. Safety data sheets are available from our website www.dymark.com.au or from the following QR code:



Call a POISON CENTRE: Australia 13 11 26, New Zealand 0800 764 766 or doctor/physician if you feel unwell.

Intentional misuse by deliberately inhaling contents can be harmful or fatal.

KEEP OUT OF REACH OF CHILDREN.

DISCLAIMER

The information provided within this Technical Data Sheet is intended as a guide only. The performance of this product will depend on many factors outside the control of Dy-Mark; including surface preparation, surface-specific conditions, surface types, correct application and environmental conditions.

Dy-Mark recommends customers undertake their own risk assessment prior to use, to determine the suitability of the product for the particular use intended.

It is essential that a sample of the product be applied to the intended area of use to ensure it is acceptable in appearance and finish and that it performs on the specific surface.

For further information please contact the Dy-Mark Sales and Customer Support Centre on 1300 396 275.