



Line Marking Paint [Solvent Based] - Bulk



Dy-Mark's Solvent-Based Line Marking Paint is a chlorinated rubber modified, alkyd-based paint designed for application over asphalt, tar sealed and concrete surfaces. The product dries fast resulting in minimal traffic holdup. The paint is easy to apply and available in a range of commonly used colours.

DIRECTIONS FOR USE

Preparation

Ensure that area to be marked is free from dust and all loosely adhered material. Wipe off contaminants such as oil and grease. The surface should be fully dry before application of the product.

Application

Stir the contents thoroughly using a broad paddle. Thin with a maximum of 5% Mineral Turps or general paint thinner if required (depending on weather conditions). Apply a uniform coat using preferred method of application, ensuring adequate build-up of film.

TECHNICAL DATA

Size:	4 Litre, 20 Litre
Finish:	Matt
Colour:	Black, Red, Blue, Green, Yellow, Orange, White, Grey
Consistency:	Liquid
Theoretical Coverage:	2.5 sqm / litre (at 200 microns dry film thickness). Actual coverage may depend on surface profile, method of application and losses
Suitable Surfaces:	Asphalt, concrete and tarsealed surfaces
Solvent Resistance:	Film is sensitive to alcohol and aromatic hydrocarbons
Drying Time (at 25°C & RH 60%):	Touch dry: 5 minutes Recoat: after 2 hours Cooler temperatures, humid conditions or a higher film thickness will require a longer drying time
Ideal Application Temperature:	Between 10°C and 40°C
Solvent for Thinning & Clean Up:	Mineral Turps or general paint thinner

STORAGE

Store below 50°C. Do not store in direct sunlight or in vehicles under hot conditions. Keep container closed when not in use.

DISPOSAL

Allow left over paint to dry and dispose of this residue in your normal rubbish. Dispose of container through an approved recycling scheme or seek advice from your local council regarding accepted disposal methods.

SAFETY INFORMATION

HIGHLY FLAMMABLE

Keep away from flame, heat and sources of ignition. Do not smoke and ensure adequate ventilation during use. Can be harmful by inhalation, in contact with skin and if swallowed. Intentional misuse by deliberately inhaling contents can be harmful or fatal.

Please note that the slip resistance and performance of this product depends on many factors outside the control of Dy-Mark; including surface preparation, correct application and environmental conditions. Dy-Mark recommends a risk assessment prior to use to determine if the product is suitable to the:

- Slip resistance required
- Surface type
- Volume of traffic
- Potential exposure to any surface contaminants e.g. water, solvents or chemicals

For more information regarding the product's slip resistance, contact Dy-Mark Sales & Customer Support Centre on 1300 396 275.

FIRST AID

KEEP OUT OF REACH OF CHILDREN

If swallowed: Do not induce vomiting.

Eye contact: In case of contact with eyes, rinse immediately with plenty of water. Seek medical advice from your doctor or Poisons Information Centre (**Australia: 13 11 26; New Zealand: 0800 764 766**).

Note: the information provided within this Technical Data Sheet is intended as a guide only. The performance of this product will depend on many factors outside the control of Dy-Mark; including surface type and environmental conditions. Refer to Material Safety Data Sheet for more information.