

Engineers Layout Ink



Dy-Mark's Engineers Layout Ink is a dye-based marking paint ideal for marking on hard surfaces such as metal and glass. Engineers Layout Ink is the ideal product for tool and die makers, machinists, pattern makers, sheet metal workers and maintenance mechanics. The coating may be scribed with lines to locate the centre of circles and shapes and to indicate areas where material is to be removed.

DIRECTIONS FOR USE

Application

Wipe Layout Ink onto the surface with a rag or apply with a brush.

TECHNICAL DATA

Size:	1 Litre
Colour:	White, Black, Red, Blue
Consistency:	Liquid
Suitable Surfaces:	Metals, glass
Drying Time:	Under 10 minutes at 25°C

STORAGE

Store below 50°C. Do not store in direct sunlight.

DISPOSAL

Allow left over paint to dry and dispose of this residue in your normal rubbish. Dispose of container through an approved recycling scheme or seek advice from your local council regarding accepted disposal methods.

FIRST AID

KEEP OUT OF REACH OF CHILDREN

If swallowed: Do not induce vomiting.

Eye contact: In case of contact with eyes, rinse immediately with plenty of water. Seek medical advice from your doctor or Poisons Information Centre (**Australia: 13 11 26; New Zealand: 0800 764 766**).

Note: the information provided within this Technical Data Sheet is intended as a guide only. The performance of this product will depend on many factors outside the control of Dy-Mark; including surface type and environmental conditions. Refer to Material Safety Data Sheet for more information.