

TECHNICAL DATA SHEET

Dy-Mark (Aust) Pty Ltd

PO Box 1556 Toowong 4066

Phone: 1300 396 275 Fax: 1300 360 440

www.dymark.com.au



Dy-Mark PROTECH® CHAIN LUBRICANT



Dy-Mark PROTECH® Chain Lubricant is a heavy duty multi-purpose chain lubricant that will resist high speed fling off while providing exceptional anti-wear and anti-corrosion performance even under the most severe operating conditions. It can work in extreme temperatures of -10degC to +155degC.

Incorporates patented 2-way actuator with locking tab.

DIRECTIONS FOR USE

Recommended Uses:

Cycle chains, chains, Pulleys, wire ropes, hoists, conveyers, chain drives, farm equipment and other uses.

Application:

Shake can for at least 45 seconds **AFTER** the mixing ball begins to rattle. Shake can occasionally during use. Spray can in **UPRIGHT** position only. Spray light even film. Use extension tube for hard to reach areas. Repeat application if necessary.

When finished spraying, actuator can be set in lock position to prevent accidental actuation.

TECHNICAL DATA

Size:	300g Aerosol
Colour:	Golden yellow
Consistency:	Liquid
Propellant:	Hydrocarbon

STORAGE

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

DISPOSAL

Dispose of contents/container according to regional regulations.

TECHNICAL DATA SHEET

Dy-Mark (Aust) Pty Ltd

PO Box 1556 Toowong 4066

Phone: 1300 396 275 Fax: 1300 360 440

www.dymark.com.au



FIRST AID / SAFETY INFORMATION

Please refer to Safety Data Sheet before use. Safety data sheets are available from our website www.dymark.com.au or from the following QR code:



Call a POISON CENTRE: Australia 13 11 26, New Zealand 0800 764 766 or doctor/physician if you feel unwell.

Intentional misuse by deliberately inhaling contents can be harmful or fatal.

KEEP OUT OF REACH OF CHILDREN.

DISCLAIMER

The information provided within this Technical Data Sheet is intended as a guide only. The performance of this product will depend on many factors outside the control of Dy-Mark; including surface preparation, surface-specific conditions, surface types, correct application and environmental conditions.

Dy-Mark recommends customers undertake their own risk assessment prior to use, to determine the suitability of the product for the particular use intended.

It is essential that a sample of the product be applied to the intended area of use to ensure it is acceptable in appearance and finish and that it performs on the specific surface.

For further information please contact the Dy-Mark Sales and Customer Support Centre on 1300 396 275.