

TECHNICAL DATA SHEET

Dy-Mark (Aust) Pty Ltd
PO Box 1556 Toowong 4066
Phone: 1300 396 275 Fax: 1300 360 440
www.dymark.com.au



Dy-Mark® METALPRO ETCH PRIMER (Grey/Black)



Dy-Mark® MetalPro Etch Primer (Grey/Black) has been designed to provide superior adhesion to metals that are difficult to bond to. **Etch Primer** provides corrosion protection and is a suitable base for a range of top coats. A fast dry product, **Etch Primer** is suitable for use on; gates, fences, railings, pipes and gutters. **Etch Primer** dries to a matt grey or black finish.

DIRECTIONS FOR USE

Suitable Surfaces:

Aluminium, galvanised iron, new steel, stainless steel, ZINCALUME®, copper and brass.

Ideal Application Temperature:

Between 10°C and 35°C. Avoid use in windy conditions.

Preparation:

MetalPro Etch Primer should not be applied to existing painted surfaces. Surface should be clean, dry and free from contaminants such as; rust, oil, grease, dirt and salt. Thoroughly sand new metal surfaces to ensure maximum adhesion and wipe down thoroughly with Acetone. For aged or lightly rusted surfaces remove loose rust with a wire brush, scraper or mechanical sander and wipe down thoroughly with Acetone. Correct surface preparation is essential for obtaining maximum coating performance.

Application:

Before spraying, cover surrounding areas to protect from overspray. **Shake can** for at least 45 seconds **AFTER** the mixing ball begins to rattle. Shake can occasionally during use. Hold can upright approximately 20-25cm from the surface. Spray with a smooth sweeping motion. To prevent paint from sagging, apply several light mist coats rather than one heavy coat. **Adjust nozzle** to achieve desired spray pattern. Use horizontal setting to spray up and down and the vertical setting to left to right.

Coverage:

Up to 2m² per can (depending on the surface and amount of overspray).

Drying Time:

Touch dry in 10 minutes (25°C).

Recoat after 2 hours.

Drying will be slower in cold and humid conditions, in the absence of ventilation or where heavy film build is applied.

After Spraying:

Prevent blocking by holding the can upside down and spraying until only clear gas escapes. Also **wipe spray tip** of nozzle clean. **Clean up** wet paint with Acetone or General Purpose Thinner.

TECHNICAL DATA SHEET

Dy-Mark (Aust) Pty Ltd
PO Box 1556 Toowong 4066
Phone: 1300 396 275 Fax: 1300 360 440
www.dymark.com.au



TECHNICAL DATA

Size:	325g Aerosol
Colour:	Grey, Black
Finish:	Matt
Consistency:	Liquid
VOC:	<680g/L
Propellant:	Dimethyl ether
Shelf Life:	4 years

STORAGE

Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in well ventilated place.

DISPOSAL

Dispose of contents/empty aerosol container according to regional regulations. Spray unwanted paint onto newspaper, allow to dry and dispose of via domestic waste collection. Empty aerosol cans are recyclable via steel can recycling programs.

FIRST AID / SAFETY INFORMATION

Please refer to Safety Data Sheet before use. Safety data sheets are available from our website www.dymark.com.au or from the following QR code:



Contact a POISONS INFORMATION CENTRE: Australia 13 11 26, New Zealand 0800 764 766 or doctor/physician if you feel unwell.
Intentional misuse by deliberately inhaling contents can be harmful or fatal.
KEEP OUT OF REACH OF CHILDREN.

TECHNICAL DATA SHEET

Dy-Mark (Aust) Pty Ltd
PO Box 1556 Toowong 4066
Phone: 1300 396 275 Fax: 1300 360 440
www.dymark.com.au



DISCLAIMER

The information provided within this Technical Data Sheet is intended as a guide only. The performance of this product will depend on many factors outside the control of Dy-Mark®; including surface preparation, surface-specific conditions, surface types, correct application and environmental conditions.

Dy-Mark® recommends customers undertake their own risk assessment prior to use, to determine the suitability of the product for the particular use intended.

It is essential that a sample of the product be applied to the intended area of use to ensure it is acceptable in appearance and finish and that it performs on the specific surface.

For further information please contact the Dy-Mark® Sales and Customer Support Centre on 1300 396 275.