

















ZINC GUARD EPOXY ENAMEL

Features & Benefits

- High build, direct to metal top coat with exceptional gloss levels
- Advanced zinc anti-corrosive formula for industrial use
- Provides a durable, long lasting finish with greater UV resistance
- Suitable for use on all metal surfaces such as: fences, gates, doors, letter boxes, fabricated steel, brackets, trailers, factory equipment and machinery

Zinc Guard Epoxy Enamel (Horizontal Spray)

	Flat Black	Flat	12	230732101
	Flat White	Flat	12	230732111
	Gloss Black	Gloss	12	230732301
	Signal Red R13	Gloss	12	230732302
	Deep Ocean	Gloss	12	230732303
	Cottage Green	Gloss	12	230732304
	Golden Yellow Y14	Gloss	12	230732305
	Classic Cream	Gloss	12	230732309
	Aluminium	Gloss	12	230732310
	Gloss White	Gloss	12	230732311
	Ultramarine B21	Gloss	12	230732314
	Jade G21	Gloss	12	230732315
	Deep Indian Red R64	Gloss	12	230732316
	Orange X15	Gloss	12	230732317



Suitable Surfaces

All metals



Coverage

Approximately 1.9 sqm per aerosol can (depending on surface and colour used)



Drying Time

Touch dry in 6 hours.
Recoat after 16 hours.
Hard dry 16–24 hours.



Ideal Application Temperature

Between 10°C and 35°C

