

TECHNICAL DATA SHEET

Dy-Mark (Aust) Pty Ltd

PO Box 1556 Toowong 4066

Phone: 1300 396 275 Fax: 1300 360 440

www.dymark.com.au



Dy-Mark P10 & P20 PAINT MARKERS



Dy-Mark P10 and P20 Paint Markers are the high performance, Xylene-free, fast drying liquid paint option for bold, easy to read marking.

Two size options, both with a reversible bullet or chisel tip, allow for application across a wide range of surfaces.

DIRECTIONS FOR USE

Suitable Surfaces:

Metal, Wood, Glass & Ceramics, Plastics, Rubber, Concrete & Stone, Waxed Paper/Cardboard.

Ideal Application Temperature:

Between -10°C and 32°C.

Before Use:

SHAKE pen well before use.

Application:

Depress tip to start paint flow.

Replace cap when not in use.

Drying Time:

5 minutes (25°C).

Mark Width:

P10: Bullet Tip 2mm
Chisel Tip 4mm

P20: Bullet Tip 3mm
Chisel Tip 5mm

After Use:

Replace Cap and push closed until click is heard

TECHNICAL DATA SHEET

Dy-Mark (Aust) Pty Ltd

PO Box 1556 Toowong 4066

Phone: 1300 396 275 Fax: 1300 360 440

www.dymark.com.au



Caution:

Painted surfaces may become slippery when wet. Refer to disclaimer on page 3.

TECHNICAL DATA

P10

Pen Dimensions:	142mm x 14mm
Colour:	Black, Red, Yellow
Contents:	10cc fast-drying, Xylene-free paint
Features:	Airtight Cap
Box Qty:	12

P20

Pen Dimensions:	135mm x 16mm
Colour:	Black, Red, Blue, Green, Yellow, Pink, White
Contents:	13cc fast-drying, Xylene-free paint
Features:	Airtight Cap with Pocket Clip
Box Qty:	12

STORAGE

Markers should be stored away from heat and light sources, and the ideal temperature is between 10°C to 32°C. They must be kept dry and in a well-ventilated area, protected from prolonged exposure to sunlight. Keep away from sources of heat and naked flames. Freezing temperatures and temperatures exceeding 50°C must be avoided.

SHELF LIFE

The shelf life is the length of storage time during which an unopened product is determined to perform consistent to their intended purpose. Stored under appropriate conditions, the standard shelf life of an unopened Dy-Mark paint pen product is 1 year from the date of purchase.

However, unopened Dy-Mark paint pen makers may be fully functional beyond the specified shelf life (for up to 3 years) depending on storage conditions and if used correctly according to their instructions. Dy-Mark has no control over the use or storage of its products once sold; therefore, we cannot assume any responsibility or liability in connection with the use, or inability to use them.

We will replace the original purchaser all products proved to be defective within one year from the date of purchase.

DISPOSAL

Dispose of contents/container according to regional regulations.

TECHNICAL DATA SHEET

Dy-Mark (Aust) Pty Ltd

PO Box 1556 Toowong 4066

Phone: 1300 396 275 Fax: 1300 360 440

www.dymark.com.au



FIRST AID/SAFETY INFORMATION

Please refer to Safety Data Sheet before use. Safety data sheets are available for download from our website www.dymark.com.au or from following QR code:



Call a POISON CENTRE: Australia 13 11 26, New Zealand 0800 764 766 or doctor/physician if you feel unwell.

Intentional misuse by deliberately ingesting contents can be harmful or fatal.

KEEP OUT OF REACH OF CHILDREN.

DISCLAIMER

The information provided within this Technical Data Sheet is intended as a guide only. The slip resistance and performance of this product depends on many factors outside the control of Dy-Mark; including surface preparation, surface-specific conditions, surface types, correct application and environmental conditions.

Dy-Mark recommends customers undertake their own risk assessment prior to use to determine the suitability of the product for the particular use intended. Some factors to consider:

- Slip resistance required
- Surface type
- Volume of traffic
- Potential exposure to any surface contaminants eg. Water, solvents or chemicals

TECHNICAL DATA SHEET

Dy-Mark (Aust) Pty Ltd

PO Box 1556 Toowong 4066

Phone: 1300 396 275 Fax: 1300 360 440

www.dymark.com.au



It is essential that a sample of the product be applied to the intended area of use to ensure it is acceptable in appearance and finish and that it performs on the specific surface.

For further information please contact the Dy-Mark Sales and Customer Support Centre on 1300 396 275.