

TECHNICAL DATA SHEET



Dy-Mark (Aust) Pty Ltd

30 Bernoulli Street Darra QLD 4076

PO Box 1556 Toowong 4066

Phone: 1300 396 275 Fax: 1300 360 440 www.dymark.com.au

Dy-Mark STEADFAST STOCK MARK



Dy-Mark Steadfast Stock Mark is a long-lasting marker ideal for identifying stock by colour coding. The fully scourable marker complies with the Australian Standard "Scourable Branding Substances for Greasy Wool" (AS4054-1992).

DIRECTIONS FOR USE

Suitable For Use On

Wool.

Code of Practice

The use of Stock Markers should be confined to the head of the animal (as outlined in the AWEX Code of Practice for Preparation of Australian Wool Clips 2016-2018). Avoid excessive application as this may result in decolourisation after scouring.

Application

SHAKE can for at least 45 seconds **AFTER** the mixing ball begins to rattle. Shake the can occasionally during use. Hold the can upright approximately 20-30cm from the surface and spray for less than 1 second.

TECHNICAL DATA

Size:	325g Aerosol
Colour:	Red, Blue, Green, Orange and Violet
Finish:	Matt
Consistency:	Liquid
Propellant:	DME

STORAGE

Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in well-ventilated place.

DISPOSAL

Aerosols should be completely emptied before disposal. Place empty can in household rubbish. Do not puncture or incinerate.

FIRST AID / SAFETY INFORMATION

Please refer to Safety Data Sheet before use. Safety data sheets are available from our website www.dymark.com.au or from the following QR code:



Call a POISON CENTRE: Australia 13 11 26, New Zealand 0800 764 766 or doctor/physician if you feel unwell. Intentional misuse by deliberately inhaling contents can be harmful or fatal. **KEEP OUT OF REACH OF CHILDREN.**

DISCLAIMER

The information provided within this Technical Data Sheet is intended as a guide only. The performance of this product will depend on many factors outside the control of Dy-Mark; including surface preparation, surface-specific conditions, surface types, correct application and environmental conditions.

Dy-Mark recommends customers undertake their own risk assessment prior to use, to determine the suitability of the product for the particular use intended.

It is essential that a sample of the product be applied to the intended area of use to ensure it is acceptable in appearance and finish and that it performs on the specific surface.

For further information please contact the Dy-Mark Sales and Customer Support Centre on 1300 396 275.