

# TREADRITE

## SLIP RESISTANT COATING

### TreadRite

- Clear
- Black
- Yellow
- Clear
- Black
- Yellow
- Clear
- Black
- Yellow

1L	1	23060100
1L	1	23060101
1L	1	23060105
4L	1	23060400
4L	1	23060401
4L	1	23060405
10L	1	23061000
10L	1	23061001
10L	1	23061005

### Slip Resistant Coating

1L, 4L & 10L | Qty 1

### Industry/Sector:

Warehousing, Commercial, Construction

## Features & Benefits

- Ideal for interior and exterior concrete, primed metal and brick & clay pavers
- Creates durable slip resistant surfaces
- Resists cracking, peeling and exposure to petrol, oil and mild chemicals
- Easy to apply with uniform coverage
- Industrial applications include stairs, entrances and exit ways
- TreadRite (1L, 4L and 10L) have been tested for compliance with AS 4586:2013, Slip resistance of new pedestrian surface materials (classification P5).

**Suitable for use on ramps.**



### Suitable Surfaces

Concrete, primed metal and brick & clay pavers



### Coverage

Yellow – approx. 3–6m<sup>2</sup>  
Clear & Black – approx. 5–10m<sup>2</sup>



### Drying Time

Touch dry 6–8 hours (25°C).  
Recoat 24–36 hours  
(depending on film thickness).  
Walk on in 24–48 hours.