

TECHNICAL DATA SHEET

Dy-Mark (Aust) Pty Ltd

30 Bernoulli Street Darra QLD 4076

PO Box 1556 Toowong 4066

Phone: 1300 396 275 Fax: 1300 360 440 www.dymark.com.au



DY-MARK TURF MASTER BULK 10L



Dy-Mark Turf Master Bulk is a Water-Based concentrate that is designed for grass surfaces and ideal for line marking Sporting Fields.

High levels of Premium Titanium Dioxide deliver an ultra-bright, whiter-than-white finish for superior coverage, opacity and visibility.

DIRECTIONS FOR USE

Suitable Surfaces:

Natural Grass / Sporting Fields *not suitable for synthetic grass.

Ideal Application Temperature:

Between 10°C and 40°C. Avoid use in windy conditions.

Preparation:

Before marking, look to clean field area of any debris. Mow grass to desired height and ensure it is dry before application.

Mixing: Recommended Dilution Rates

White:

Up to (1:4) Mix up to 1 part paint to 4 parts water for initial marking applications

Up to (1:6) Mix up to 1 part paint to 6 parts water for overmarking applications

Black:

Up to (1:2) Mix up to 1 part paint to 2 parts water for initial marking applications

Up to (1:3) Mix up to 1 part paint to 3 parts water for overmarking applications

TECHNICAL DATA SHEET

Dy-Mark (Aust) Pty Ltd

30 Bernoulli Street Darra QLD 4076

PO Box 1556 Toowong 4066

Phone: 1300 396 275 Fax: 1300 360 440 www.dymark.com.au



Application:

Turf Master paint can be applied by suitable spray machines, transfer wheel markers, brush and roller.

Mark the lines carefully using string line or a suitable marking tool to ensure accuracy.

Apply the paint evenly along the marked lines, keeping a steady pace and consistent pressure for smooth, uniform coverage.

For optimal visibility, apply 2-3 coats allowing each coat to dry fully before applying the next coat.

Avoid application during extreme temperatures or excessively humid or damp conditions.

Coverage:

Coverage will vary depending on equipment and rate of application.

Drying Time:

Approximately 15-20 minutes dry time. Recoat in 1 hour.

Cooler conditions may result in longer dry & recoat times.

Clean Up:

Clean all tools & equipment with water immediately after use before product has a chance to cure.

TECHNICAL DATA

Synonyms:	41201001 / 41201011
Size:	10L
Colour:	Black & White
Consistency:	Liquid
Shelf Life:	2 years from date of manufacture

STORAGE

Store locked up. Store in a well-ventilated place. Keep cool. Keep container tightly closed.

DISPOSAL

Dispose of contents/container to authorised hazardous or special waste collection point according to local regulations. Do not pour unwanted paint down the drain. Keep unwanted paint in sealed containers for disposal via chemical waste collections. Empty paint containers

TECHNICAL DATA SHEET

Dy-Mark (Aust) Pty Ltd

30 Bernoulli Street Darra QLD 4076

PO Box 1556 Toowong 4066

Phone: 1300 396 275 Fax: 1300 360 440 www.dymark.com.au



should be left open in a well ventilated area to dry out. When dry, empty containers are recyclable in accordance with local regulations.

FIRST AID / SAFETY INFORMATION

Please refer to Safety Data Sheet before use. Safety data sheets are available from our website www.dymark.com.au or from the following QR code:



Contact a POISONS INFORMATION CENTRE: Australia 13 11 26, New Zealand 0800 764 766 or doctor/physician if you feel unwell.
KEEP OUT OF REACH OF CHILDREN.

DISCLAIMER

The information provided within this Technical Data Sheet is intended as a guide only. The performance of this product will depend on many factors outside the control of Dy-Mark; including surface preparation, surface-specific conditions, surface types, correct application, and environmental conditions.

Dy-Mark recommends customers undertake their own risk assessment prior to use, to determine the suitability of the product for the particular use intended.

It is essential that a sample of the product be applied to the intended area of use to ensure it is acceptable in appearance and finish and that it performs on the specific surface.

For further information please contact the Dy-Mark Sales and Customer Support Centre on 1300 396 275.