

TECHNICAL DATA SHEET

Dy-Mark (Aust) Pty Ltd
PO Box 1556 Toowong 4066
Phone: 1300 396 275 Fax: 1300 360 440
www.dymark.com.au



Dy-Mark Protech Multi-Purpose Lubricant



Dy-Mark Protech Multi-Purpose Lubricant penetrates and loosens rust and corrosion for easy removal. It cleans dirt and scale while protecting metal surfaces against corrosion. The formula lubricates moving parts to ensure smooth operation and eliminates squeaks. It repels moisture, helping to start wet engines. Additionally, it reduces the need for complex disassembly, making maintenance more efficient.

DIRECTIONS FOR USE

Suitable Surfaces:

Metal

Ideal Application Temperature:

Between 20°C and 30°C.

Preparation:

Before applying Protech bulk Multi-Purpose Lubricant, ensure proper preparation for optimal performance.

First, clean the surface thoroughly to remove dirt, debris, and any old lubricant residue, preventing contamination.

To displace water, spray thoroughly onto wet surfaces until the runoff appears clear, ensuring the surface is clean of any residue. Inspect components for signs of wear, corrosion, or damage to confirm they are in good condition.

Apply the lubricant at the recommended temperature to ensure proper viscosity and penetration. Use appropriate dispensing equipment for even coverage across the surface. Finally, work in a well-ventilated area and follow all safety guidelines for handling lubricants.

Application:

Do not spray when the equipment is energised. Spray from approximately 20 to 25cm distance for optimal coverage. This can be applied with a suitable atomiser spray bottle. Apply in light even coats to protect surfaces. Generously apply to rusted or seized parts to aid in loosening, allowing several hours for full penetration.

After handling, thoroughly wash any contacted areas. Use the product in a well-ventilated space.

Brush:

Clean the surface to remove dirt. Dip the brush lightly into the lubricant and apply evenly with smooth strokes on the targeted area. Allow lubricant to settle as recommended and wipe off excess.

Coverage:

Approximately 80-90m² per litre

TECHNICAL DATA SHEET

Dy-Mark (Aust) Pty Ltd

PO Box 1556 Toowong 4066

Phone: 1300 396 275 Fax: 1300 360 440

www.dymark.com.au



Clean Up:

Clean brushes & equipment with mineral spirits, scrub if needed or wash with soapy water and dry thoroughly.

TECHNICAL DATA

Synonyms:	42040402 / 42042002
Size:	4L & 20L
Colour:	Clear Amber Liquid
Shelf Life:	3 years from date of manufacture
Consistency:	Liquid

STORAGE

Store locked up. Store in a well-ventilated place. Keep cool. Keep container tightly closed.

CAUTION: Open carefully wearing gloves and eye protection.

DISPOSAL

Dispose of contents/container according to regional regulations. Do not pour unwanted product down the drain. Keep unwanted product in sealed containers for disposal via chemical waste collections. Empty containers should be left open in a well-ventilated area to dry out. When dry, empty containers are recyclable in accordance with local regulations.

FIRST AID / SAFETY INFORMATION

Please refer to Safety Data Sheet before use. Safety data sheets are available from our website www.dymark.com.au or from the following QR code:



Contact a POISONS INFORMATION CENTRE: Australia 13 11 26, New Zealand 0800 764 766 or doctor/physician if you feel unwell.
KEEP OUT OF REACH OF CHILDREN.

DISCLAIMER

The information provided within this Technical Data Sheet is intended as a guide only. The performance of this product will depend on many factors outside the control of Dy-Mark; including surface preparation, surface-specific conditions, surface types, correct application and environmental conditions.

TECHNICAL DATA SHEET

Dy-Mark (Aust) Pty Ltd

PO Box 1556 Toowong 4066

Phone: 1300 396 275 Fax: 1300 360 440

www.dymark.com.au



Dy-Mark recommends customers undertake their own risk assessment prior to use, to determine the suitability of the product for the particular use intended.

It is essential that a sample of the product be applied to the intended area of use to ensure it is acceptable in appearance and finish and that it performs on the specific surface.

For further information please contact the Dy-Mark Sales and Customer Support Centre on 1300 396 275.